

## ASK Proxima C200 (DP6500x) Projector

### Technical and Functional Specifications

General	
Aspect Ratio	4:3
Contrast Ratio	800:1
Data Compatibility	SXGA, XGA, SVGA, VGA, Macintosh®, and 1080i/720p HDTV
Display	DLP™ by Texas Instruments 0.7" XGA DMD DDR
Image Size (diagonal)	2.4' to greater than 22' 0.7m to greater than 6.7m
Light Source	250-Watt UHP, 2000 hours life
Native Resolution	XGA (1024x768)
Projection Lens	Manual zoom lens
Projection Methods	Front, rear, and ceiling
Throw Ratio	0.48 – 0.67:1 (Diagonal Image/Distance) 1.88 – 2.63:1 (Horizontal Image/Distance)
Projection Offset	115.2%
Video Compatibility	Full NTSC, PAL, SECAM, EDTV, (480p, 576p), HDTV (720p, 1080i)
Minimum Projection Distance	5' / 1.5m
Size	
Dimensions	4.3" (H) x 13.8" (W) x 12.8" (L) 11cm x 35cm x 32.5cm
Weight	9.35 lbs. 4.24 kg
Input	
Digital Keystone Correction	+/- 20 degrees
Input Sources	Computer 1 (M1-D/A with 3.5mm audio), computer 2 (VESA with 3.5mm audio), video 1 (S-Video), video 2 (RCA), video 3 (component RCA), stereo audio (RCA), RS-232, NIC (RJ45)
Output	
Audio	2 x 2 Watt stereo
Brightness	2500 ANSI lumens
Color Palette	16.7 million
Projection	Distance to Screen: 5.0' (1.5m) 10.0' (3.0m) 15.0' (4.6m)
Distances/Image Sizes	20.0' (6.1m) 30.0' (9.1m) 32.8' (10.0m) Min. Diagonal: 0.48 Throw Ratio 2.4' (0.7m) 4.8' (1.5m) 7.2' (2.2m) 9.6' (2.9m) 14.4' (4.4m) 15.7' (4.8m) Image Diagonal: 0.67

	Throw Ratio 3.4' (1.0m) 6.7' (2.0m) 10.1' (3.1m) 13.4' (4.1m) 20.1' (6.1m) 22.0' (6.7m) Min. Horiz. Image Size: 1.88 Throw Ratio 1.9' (0.6m) 3.8' (1.1m) 5.7' (1.7m) 7.6' (2.3m) 11.4' (3.5m) 12.5' (3.8m) Max. Horiz. Image Size: 2.63 Throw Ratio 2.7' (0.8m) 5.3' (1.6m) 8.0' (2.4m) 10.6' (3.2m) 15.9' (4.8m) 17.4' (5.3m) *Metric conversions are approximate
<b>Other</b>	
Brightness Uniformity	+30/-40
Colorwheel Speed	7200 RPM
H-Sync Range	50-117Hz
V-Sync Range	50-85Hz
Operating Temperature	10° - 40° C at sea level (0 – 10,000'); 50° - 104° F
Power Consumption	350 Watts
Power Supply	100V – 240V at 50-60Hz
Ships Standard With	Exclusive Organizer molded carry case, Conductor™ Plus full-featured remote with laser pointer, color-coded cable straps, M1 D/A analog computer cable with USB, 3.5mm computer audio cable, RCA audio/video cable, power cord, user manual, quick start card, and informational CD
Warranty	2 years part and labor, 1 year accessories
Lamp Warranty	90 days or 500 hours
Menu Languages	English, Spanish, French, German, Japanese, Korean, Portuguese, Italian, Norwegian, Russian, Chinese Simple, Chinese Traditional